White Graphene Enhanced Thermal Grease

Key findings:

White Graphene (WG) enables prominent performance enhancement in thermal grease at 0.5% loadings:

- Thermal conductivity: **+ 38%** (5.78 to 7.98 W/m*K) hard
  + 24% (5.91 to 7.31 W/m*K) soft





White Graphene

A novel two-dimensional layered nanomaterial - BNNS







PRODUCT CHARACTERISTICS	METHDOLOGY	STANDARD
Appearance	Visual	White solid powder
Lateral Size	Scanning Electron Microscope	0.3-10 µm
Lateral Aspect ratio	Scanning Electron Microscope	1:1 - 1:30
Thickness	Atomic Force Microscope	1-50 nm
Bulk density	EN17199-1 weighting method	0.055 g/cm³
Respirable dustiness fraction	EN17199 Small Rotating drum (M4)	55 mg/kg
Water solubility	OECD 105 Flask Method	Insoluble
	Raman Spectroscopy	BN vibrational peak
	Fourier-transform infrared spectroscopy	BN vibrational peaks
Chemical composition and Impurities	Energy-Dispersive X-ray Spectroscopy	B & N > 98% O < 2% Other < 0.5%
Surface functionalization	-	Customized

P: +61 (0) 7 3054 4500
E: info@white-graphene.com
W: white-graphene.com

Level 13, 120 Edward Street,
Brisbane QLD 4000
Australia